

polypropylene

Homopolymer 6345 Fiber Resin

Grade 6345 is a low water carryover polypropylene homopolymer for fiber and tape applications. This material meets the requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520.

Applications

- Carpet backing
- Fiber bags
- Fiber and tape
- Rope and cordage
- Twine

Benefits

- Low water carryover

Typical Properties*

Resin	Value	ASTM Method
Melt Flow Rate, 2.16 kg at 230°C, g/10 min	3.2	D1238
Injection Molded Sample		
Tensile at 23°C		D638
Strength at Yield, psi (MPa)	5,300 (36)	
Elongation at Yield, %	10	
Elongation at Break, %	>200	
Flexural Modulus, at 23°C, kpsi (MPa)	185 (1,280)	D790A
Heat Deflection Temperature at 66 psi, (455 kPa), °F (°C)	200 (93)	D648

* Typical properties will vary within specification limits.



Regulatory Information

The product and uses described herein may require global product registrations and notifications for chemical inventory listings, or for use in food contact or medical devices. For further information, send an e-mail to: bpcares@bp.com.

Health and Safety Information

The product described herein may require precautions in handling and use because of toxicity, flammability, or other consideration. The available product health and safety information for this material is contained in the Material Safety Data Sheet (MSDS) that may be obtained by calling +1-866-427-6737 (Toll Free-North America), or by sending an e-mail to: bpcares@bp.com. Before using any material, a customer is advised to consult the MSDS for the product under consideration for use.

The Material Safety Data Sheet for this product contains shipping descriptions and should be consulted, before transportation, as a reference in determining the proper shipping description. If the material shipped by BP is altered or modified, different shipping descriptions may apply and the MSDS of the original material should not be used.

For additional information, samples, pricing and availability, please contact:

BP Amoco Chemical Company

Sales Administration and Customer Service

150 West Warrenville Road

Naperville, Illinois 60563-8460

Toll-free: 877/701-2726

Fax: 630/961-7700

email: chem_americas@bp.com

Technical information contained herein is furnished without charge or obligation, and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, BP makes no representation about, and is not responsible or liable for the accuracy or reliability of data, nor for toxicological effects or Industrial Hygiene requirements associated with particular uses of any product described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item not supplied by BP. The "Properties" and "Applications" listed in this document are not specifications. They are provided as information only and in no way modify, amend, enlarge, or create any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED.