

Polyethylene mPE M 3020

Content:

- Technical Data Sheet
- Regulatory Certificate
 - Statement of compliance for food contact applications
 - Statement on toys
 - Statement on Transmissible Bovine Spongiform Encephalopathy (BSE) and Genetically Modified Organisms (GMO)
 - Statement on inventories

For other Regulations, please consult our Product Stewardship Certificate available on this website. We have included in our Polyethylene Product Stewardship Certificate the conformity to a number of regulations whenever it could be certified for all our European polyethylene products.

In case you might need additional technical or regulatory information, please contact your sales representative.

Description

mPE M 3020 is a second generation metallocene based Polyethylene resin with hexene as comonomer.

mPE M 3020 can be processed at high output rates with low extrusion pressure and good gauge control in comparison with conventional LLDPE and first generation metallocene based polyethylene. The combination of these features brings a significant downgauging potential.

mPE M 3020 is especially dedicated to film applications where high gloss and good transparency are required, particularly in blend and coextrusion with LLDPE or LDPE.

mPE M 3020 is suited for many applications in the field of consumer, automatic, food or hygiene packaging.

Characteristics

Property	Method	Unit	Typical value
Density	ISO 1183	g/cm ³	0.930
Melt Flow Rate (190°C/2.16 kg)	ISO 1133	g/10 min	2.0
Melting temperature	ISO 11357	°C	120
Vicat temperature	ISO 306	°C	119

Values indicated are typical for this product. Density and MFR are properties routinely measured during "the standard quality control procedure". The other figures are generated by tests not included in the "standard quality control procedure", and are given for information only. Data are not intended for specification purposes.

Processing

On a blown film line mPE M 3020 is typically extruded at a melt temperature around 200°C. mPE M 3020 can be blown easily at any of the following conditions:

- Temperature: 180 to 230°C
- BUR : 1.5:1 to 4.5:1
- Die gap : 0.8 to 2.8 mm

An excellent blending ability of mPE M 2310 EP with LDPE and LLDPE is observed.

On a cast film line mPE M3020 can be easily extruded in the following conditions:

- Melt temperature : 240 to 280°C
- Chill roll temperature : 20 to 60 °C

Additives

Antioxidant : yes

PPA : no

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.

Blown film properties

Blown film values have been measured on a 40 µm film and cast film values on a 20 µm film.

Property	Method	Unit	Typical blown film value (*)	Typical cast film value (**)
Tensile Strength at Yield MD/TD	ISO 527-3	MPa	15/15	11.0/10.8
Tensile Strength at Break MD/TD	ISO 527-3	MPa	36/38	52/33
Elongation at Break MD/TD	ISO 527-3	%	610/710	480/640
Elmendorf MD/TD	ISO 6383-2	N/mm	37/140	32/150
Dart test	ISO 7765-1	g	95	73
Haze	ISO 14782	%	8	1.7
Gloss 45°	ASTM D2457		64	89

(*) Figures stated hereabove are obtained using laboratory test specimens produced with the following extrusion conditions: 45 mm screw diameter, L/D = 30, die diameter = 120 mm, die gap = 1.4 mm, BUR = 2.5:1, temperature = 210°C.

(**) Figures stated hereabove are obtained using laboratory test specimens produced at the following extrusion conditions: die gap = 250 µm, chill roll temperature = 20°C, throughput = 7 kg/h, melt temperature = 260 °C

Handling and storage

Please refer to the safety data sheet (SDS) for handling and storage information. It is advisable to convert the product within one year after delivery provided storage conditions are used as given in the SDS of our product. SDS may be obtained from the website: www.totalpetrochemicals.biz

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.



TOTAL PETROCHEMICALS RESEARCH FELUY
Industrial Property & Regulatory Affairs Department
Regulatory Affairs
Tel : +32 (0)64 51 40 10
Fax : +32 (0)64 51 41 49
petrochemicals.felr-regaffairs@total.com

Feluy, March 10, 2009

POLYETHYLENE - mPE M3020

STATEMENT OF COMPLIANCE FOR FOOD CONTACT APPLICATIONS :

In the EUROPEAN UNION

We confirm that the above-mentioned Product fulfils the harmonised requirements on materials used for articles or components of articles intended to come into contact with food as described in the European Directive 2002/72/EC amended by Directives 2004/1/EC, 2004/19/EC, 2005/79/EC, 2007/19/EC, 2008/39/EC and its transposition into national laws as incorporated in the following contact regulations:

in Belgium :

- Arrêté Royal du 03/07/2005 concernant les matériaux et objets destinés à entrer en contact avec les denrées alimentaires (Moniteur Belge du 29/07/2005).
- Arrêté Royal du 05/07/2006 (Moniteur Belge du 07/09/2006) modifiant l'Arrêté Royal du 3/07/2005.

in France :

- Décret Ministériel n° 73-138 du 12/02/73 et n° 2007-766 du 10/05/2007 ainsi que les lettres circulaires de la Répression des Fraudes et contrôle de la qualité (Recueil de textes: brochure n° 1227 "Matériaux au contact des aliments et denrées destinées à l'alimentation humaine" - dernière édition : 15/07/2002);
- Instruction relative à l'emploi d'additifs dans les matières plastiques au contact des denrées alimentaires (Bulletin Officiel de la concurrence, de la consommation et de la répression des fraudes du 11/08/93);
- Arrêté du 19/10/2006 modifiant l'arrêté du 02/01/2003 relatif aux matériaux et objets en matière plastique mis ou destinés à être mis au contact avec les denrées, produits et boissons alimentaires.

in Germany :

- Gesundheitliche Beurteilung von Kunststoffen im Rahmen des Lebensmittel- und Bedarfsgegenständegesetzes (BfR) : Empfehlung III : Polyethylen Stand 01/06/2007 - 210 Mitteilung - B. Gesundh. Bl. 50 (2007) 1470.
- Bedarfsgegenstandsverordnung (BGV) vom 10. April 1992 (BGBl.I.S.866) und Änderungen vom 11. April 1993 (BGBl.I.S.775) , vom 17. April 1997 (BGBl.I.S.796) und vom 21. Dezember 2000 (BGBl.I.S.1886), vom 7. April 2003(BGBl I.S. 486), vom 6.September 2005 (BGBl.I.S.2618) und vom 26 April 2006 (BGBl. I.S. 945)

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. **Under no circumstances are any products sold by Total Petrochemicals suitable for human or animal implants.**

The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.



TOTAL PETROCHEMICALS RESEARCH FELUY
Industrial Property & Regulatory Affairs Department
Regulatory Affairs
Tel : +32 (0)64 51 40 10
Fax : +32 (0)64 51 41 49
petrochemicals.felr-regaffairs@total.com

CERTIFICATE N° 33437

Feluy, March 10, 2009

POLYETHYLENE - mPE M3020

in Italy :

- Decreto Ministeriale 21/03/1973 (G.U. n° 104 - 20/4/1973) Disciplina igienica degli imballaggi, recipienti, utensili, destinati a venire in contatto con le sostanze alimentari o con sostanze d'uso personale as amended by Decree of the Ministry of Health N°411 of 1/12/2000 (G.U. N°11-15/01/2001)
- Decreto Ministeriale 26/04/1993, n°220 (G.U. n° 162 - 13/7/1993) Regolamento recante aggiornamento del decreto ministeriale 21/03/1973, concernente la disciplina igienica degli imballaggi, recipienti, utensili destinati a venire in contatto con le sostanze alimentari e con sostanze d'uso personale as updated up to D.M.H n° 82 of 18/04/2007 (G.U. N°151 - 02/07/2007).

in Spain :

- Orden SCO/ 983/ 2003 de 15 de abril (B.O.E. n° 99 de 25/04/2003) .
- Resoluciones del Ministerio de Sanidad de 04.11.1982 (B.O.E. n° 282 de 24.11.1982).
- Orden del Ministerio de Sanidad de 03.07.1985 (B.O.E. n° 166 de 12.07.1985).
- Real Decreto 2207/94 de 16/11/1994 as updated to R.D. 442/2001.
- Real Decreto 118/2003 de 31/01/2003 as updated to R.D. 866/2008.

in the United kingdom :

- The Plastic Materials and Articles in Contact with Food Regulations - 2008
- England: Statutory Instruments 2008/916
- Northern Ireland: Statutory Rules 2008/167
- Scotland: Statutory Instruments 2008/127
- Wales: Statutory Instruments 2008/1237 (W.124)

Conditions:

- Regarding overall migration:

According to the Directives 82/711/EEC (and its amendments 93/8/EEC and 97/48/EEC), 85/572/EEC and 2002/72/EC, the overall migration limit, for which a maximum value of 10 mg/dm² or 60 mg/kg is set (Directive 2002/72/EC, article 2) , has to be controlled on the finished articles intended to come into contact with foodstuffs; consequently it is the responsibility of the end-user of the above-mentioned Product.

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. **Under no circumstances are any products sold by Total Petrochemicals suitable for human or animal implants.**

The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.



TOTAL PETROCHEMICALS RESEARCH FELUY
Industrial Property & Regulatory Affairs Department
Regulatory Affairs
Tel : +32 (0)64 51 40 10
Fax : +32 (0)64 51 41 49
petrochemicals.felr-regaffairs@total.com

Feluy, March 10, 2009

POLYETHYLENE - mPE M3020

Specific Migration Limit(s):

Restriction for Monomer ^{a)} :

1- Hexene (CAS RN : 00592-41-6 - PM Ref : 18820 - Status : SML= 3 ppm)

Restriction for Additives ^{b)}: none

- European Directive 2004/19/EC and its transposition into national laws.

We inform you that we do not use food additives as authorized by and subject to a restriction in the European Directive 89/107/EC and/or flavorings as authorized by the European Directive 88/388/EC during the manufacturing of the above-mentioned product. However, since we do not perform specific tests to verify the potential presence of any of these food additives, we cannot guarantee that there is no trace amount of some of these substances, as impurity or otherwise, in the above-mentioned product.

REGULATION 1935/2004/EC

We hereby confirm that the above-mentioned Product, when used under normal or foreseeable conditions of use, meets the relevant requirements laid down in Regulation 1935/2004/EC.

REGULATION 2023/2006/EC (GMP)

We inform you that the production of the above-mentioned Product is systematically reviewed with regards to good manufacturing practice (GMP) using our ISO 9001 System, and following the Plastics Europe guideline specifically dedicated to GMP.

Therefore we can state that the above-mentioned Product meets the relevant requirements laid down in Regulation 2023/2006/EC.

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. **Under no circumstances are any products sold by Total Petrochemicals suitable for human or animal implants.**

The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.



TOTAL PETROCHEMICALS RESEARCH FELUY
Industrial Property & Regulatory Affairs Department
Regulatory Affairs
Tel : +32 (0)64 51 40 10
Fax : +32 (0)64 51 41 49
petrochemicals.felr-regaffairs@total.com

CERTIFICATE N° 33437

Feluy, March 10, 2009

POLYETHYLENE - mPE M3020

in the UNITED STATES OF AMERICA :

- Code of Federal Regulations Food and Drugs Title 21 (2008) §177.1520 : Olefins Polymers;(a) (3) (i) (a) (1), (b) and (c) 3.2a.. The above-mentioned Product meets the criteria in §176.170(c), with food types I through IX of Table 1, under conditions of use A through H of Table 2.

GENERAL USE CONDITIONS :

it pertains to end-users of materials intended to come into contact with food, to ensure that the material does not bring about an unacceptable change in the composition of the food, or bring about a deterioration in the organoleptic characteristics which render it unfit.

STATEMENT ON TOYS - EUROPEAN STANDARD EN 71- 3.1994 and EN 71- 9.2005 :

We hereby confirm that the above-mentioned Product meets the requirements of European Standard EN 71-3 1994 its amendment EN 71- 3/ A1 2000 corrigendum AC: 2002 entitled "Safety of Toys - Part 3 : Migration of certain elements" and EN 71-9, September 2005 "Organic chemical compounds- requirements".

The above-mentioned Product meets this standard because every time analyses were performed on this product, results were below the prescribed limits.

STATEMENT ON TRANSMISSIBLE BOVINE SPONGIFORM ENCEPHALOPATHY (BSE) :

We hereby confirm that we did receive an indication from our suppliers of additives (by additive is meant a substance which is incorporated into plastics to achieve a technical effect in the finished product) used in the above-mentioned Product mentioning the absence of any substances which are of animal origin. Based on the above, we are confident that the above-mentioned Product are free of SRM (Specified Risk Materials).

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. **Under no circumstances are any products sold by Total Petrochemicals suitable for human or animal implants.**

The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.



TOTAL PETROCHEMICALS RESEARCH FELUY
Industrial Property & Regulatory Affairs Department
Regulatory Affairs
Tel : +32 (0)64 51 40 10
Fax : +32 (0)64 51 41 49
petrochemicals.felr-regaffairs@total.com

Page 5/5

CERTIFICATE N° 33437

Feluy, March 10, 2009

POLYETHYLENE - mPE M3020

STATEMENT ON GENETICALLY MODIFIED ORGANISMS (GMO).

We hereby confirm that we did receive an indication from our suppliers of additives ^{b)} used in the above-mentioned Product mentioning the absence of any Genetically Modified Organisms (GMO).

STATEMENT ON INVENTORIES:

We declare that the monomers and, if present, the additives ^{b)} of the above-mentioned Product are listed or exempted from listing on:

AICS, ECL, EINECS AND/OR ELINCS, ENCS, PICCS and TSCA.

NOTE :

a) Monomer as defined in the EC Directive 2002/72/EC up to 2008/39/EC.

b) Additive as defined in the EC Directive 2002/72/EC up to 2008/39/EC.

DISCLAIMER :

Our certificate does not cover:

- any modification of the the above-mentioned Product by any addition of any other product or Ingredient to it;
- any prejudicial modification of the above-mentioned Product resulting from a processing of it;
- an inadequate use and/or storage of the above-mentioned Product and/or of the finished articles.

The present certificate is valid until end 2009. Upon the expiration of this certificate, we can issue a new one at your request. In case of change during this period a new certificate will be issued automatically; kindly forward it to any recipient of the present certificate.

TOTAL PETROCHEMICALS RESEARCH FELUY

C. RAIMOND
Regulatory Affairs

F. WYLIN
Regulatory Affairs, Manager

Issued by an electronic system

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. **Under no circumstances are any products sold by Total Petrochemicals suitable for human or animal implants.**

The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.



TOTAL PETROCHEMICALS RESEARCH FELUY
Société Anonyme
Zone Industrielle C – B-7181 FELUY
Tel : +32 (0)64 51 41 11
Fax : +32 (0)64 54 08 65

RPM Charleroi: 0.438.021.316
TVA : BE 438.021.316
Banque : 210-0473820-27